

# Vege-Kleen™ 2000 Vegetable Sanitizing System

## Important Safety Instructions

1. Do not operate this unit if it has a damaged cord or plug, or after a malfunction.
2. Follow installation instructions.
3. Only use a cold water supply.
4. Inlet water pressure should not exceed 85 PSI with a minimum of 25 PSI. In-excess of 85 PSI will damage unit and void the warranty. A water pressure regulator may be needed (not supplied).
5. If the unit requires servicing, always turn off the water supply and disconnect the power supply before removing the unit. Do not try to attempt to repair the unit yourself. Only qualified service personnel should service this unit and your warranty will be voided if you open the unit.



## Installation Instructions

1. Following the instructions inside the faucet package to install the faucet to the sink or counter top.
2. Under the sink, locate the cold water supply and turn it off. Remove the water supply line to the sink at the supply (angle stop). Install the 3/8" faucet adapter (or a similar adapter available at your local hardware store) and reconnect the supply line to the sink.
3. Attach the Vege-Kleen to the side of the cabinet with the included mounting screws (near an 120V power supply and water supply - you will need a dedicated power outlet).
4. Insert the 3/8" tubing into the faucet adapter. Cut the tubing to size that will fit your space requirement and insert the tubing into the Vege-Kleen IN port which is located on the side of the unit. Make sure the tubing seats all the way into the housing.
5. Bring 3/8" tubing from the faucet to the OUT port of the Vege-Kleen which is located on the opposite side of the IN port.
6. Open the water supply slowly and check for leaks. Open the faucet to purge system.
7. Plug the power cord into the Vege-Kleen and then into the power supply.
8. Open the faucet completely and allow the water to run for at least three seconds. Fill a glass with water from the Vege-Kleen and test the water by dipping the test strip into the water. Keep the strip in the water for 10 seconds moving it back and forth (you should smell a small amount of Ozone). Shake off the strip once, wait 20 seconds and then you should find that the test strip changes color from yellowish brown to green. This change indicates the presence of ozone.

## Specifications

- Power: 120V AC 60 Hz
- Flow rate: 1.5 GPM at 50 PSI
- Max. & min. water pressure: 85 & 25 PSI
- Ozone output: up to 400 mg/hr
- Ozone residual: up to 0.7ppm
- Dimensions: (L) 11.75" (W) 5.5" (H) 4"
- Weight: 4 lbs

## Features

- All internal components are UL listed
- Solid-state electronics encased in epoxy
- Simple installation
- Activation as faucet is opened and closed
- Small compact design
- State-of-the-art venturi injector and O<sub>3</sub> generator
- Quiet operation

---

We hope you enjoy using your Model Vege-Kleen 2000. For more information on this product or any other air or water ozone products, please contact your Distributor.

## Parts List

- (1) faucet & installation instructions
- (1) 120V power supply cord
- (1) 6 Feet of  $\frac{3}{8}$ " tubing
- (1)  $\frac{3}{8}$ " faucet adapter (if needed other sizes are available at your local hardware store)
- (3) ozone present test strips
- (2) mounting screws

## Warranty

One Year

