

# MODEL 2500 120V- KLEENAIR OPERATING INSTRUCTIONS

## PRODUCT OVERVIEW

The Model 2500 - Kleenair is designed for general purpose applications such as homes, small offices, beauty shops, boats, hotel rooms, RV's and mobile homes where space is confined and the odor problems are moderate to severe. The Model 2500 - Kleenair is ideal in situations of high humidity, continuous sources of pollution or where unusually persistent odors exist. It is enclosed in an all aluminum case for those rugged jobs and will treat an area up to 2500 sq. ft. This unit duplicates the clean fresh mountain air that occurs naturally outdoors by utilizing ultra violet light to convert oxygen to ozone. Science has proven ozone to be one of the most powerful oxidizing agents known to man.



## IMPORTANT SAFETY INSTRUCTIONS

- This unit should be used in **UNOCCUPIED AREAS** only.
- To protect against risk of electric shock and personal injury, do not place cord, plugs or the unit in or near water/liquid.
- Do not operate this unit if it has a damaged cord or plug, or after a malfunction. Handle the cord carefully for longer life.
- Do not place the unit near an open flame. This unit is not intended for outdoor use.
- Do not cover or block any openings on the unit.
- Do not try to repair the unit yourself. Only qualified service personnel should service this unit and your warranty will be voided if you open the unit.

## OPERATING INSTRUCTIONS

- Place the Model 2500 - Kleenair unit in a location that allows the ozone to spread evenly and be thoroughly mixed with the untreated air. If possible recirculate the air around the area while the unit is running for optimal treatment.
- Elevate the Model 2500 - Kleenair unit as high as possible to ensure better coverage. To achieve an unrestricted airflow, keep the unit at least four inches away from the wall.
- The air coming out of the exhaust ports on the top of the unit should be directed away from people, pets and plants.
- To keep the unit running indefinitely, turn the timer dial 'counter clockwise' to the 'on continuous' setting. The unit will stay on until manually turned off.
- To keep the unit running for up to one hour, turn the timer dial clockwise to your desired length of time.
- Located beneath the Model 2500 - Kleenair is a filter. Rinse off filter with water as needed and allow to dry.

## SPECIFICATIONS

- Ozone Output: 22 PPM
- Ozone concentration produced by UV bulb
- Power: 120V AC
- Electrical draw: 0.4 Amp
- Fuse: 2.0 Amp
- Fan volume: 105 CFM
- Dimensions: (L) 13.5" (W) 6" (H) 9"
- Weight: 5 lbs.
- Coverage: 2500 sq. ft.

SUGGESTED OPERATING TIMES:	
Cigarette smoke	30 - 60 minutes
Cigar smoke	60 minutes
Mold / mildew	24 - 72 hours
Pet urine	48 hours

## FEATURES

- User friendly
- Energy efficient
- Electronic ballast
- Aluminum construction
- Virtually maintenance free

## WARRANTY

- One year
- Excellent Customer Support Team

We hope you enjoy using your Model 2500 120V - Kleenair. For more information on this product or any other air or water ozone products, please contact your Distributor.