

Model 2500 240V – Kleenair Operating Instructions

Important safety instructions

- This unit should be used in **UNOCCUPIED AREAS** only.
- To protect against risk of electric shock and personal injury, do not place cord, plugs or the unit in water or any other liquid.
- Do not operate this unit if it has a damaged cord or plug, or after a malfunction.
- This appliance is not intended for outdoor use.
- Handle the cord carefully for longer life.
- Do not cover or block any openings on the unit.
- Do not place the unit near an open flame.
- Do not try to repair the unit yourself. Only qualified service personnel should service this unit and your warranty will be voided if you open the unit.



Operating instructions

- Elevate the Kleenair unit as high as possible to ensure better coverage. To achieve an unrestricted airflow, keep the unit at least four inches away from the wall.
- The air coming out of the exhaust ports on top of the unit should be directed away from people, pets and plants.
- To keep the unit running indefinitely, turn the timer dial 'counter clockwise' to the 'on continuous' setting. The unit will stay on until manually turned off.
- To keep the unit running for up to one hour, turn the timer dial clockwise to your chosen number of minutes.

Specifications

- Ozone Output: 100mg/hr
- Power: 240V AC
- Electrical draw: 0.4 Amp
- Fuse: 2.0 Amp
- Fan volume: 105 CFM
- Ozone concentration produced by UV bulb
- Dimensions: (L) 13.5" (W) 6" (H) 9"
- Weight: 5lbs.
- Coverage: 2500 sq. ft.

Features

- User friendly
- Energy efficient
- Electronic ballast
- Aluminum construction
- Virtually maintenance free

Warranty

- One year

Suggested operating times:	
Cigarette smoke	30 - 60 minutes
Cigar smoke	60 minutes
Mold / mildew	24 - 72 hours
Pet urine	48 hours

We hope you enjoy using your Model 2500 Kleenair. For more information on this product or any other air or water ozone products, please contact your Distributor.